

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

Please cancel claims 1 and 7 without prejudice.

Please add new claims 8-10.

Please amend claims 2 and 6 as indicated below (material to be inserted is in underline, material to be deleted is in ~~strikeout~~):

**Listing of Claims:**

1. (Cancelled)
2. (Currently Amended) ~~The apparatus of claim 1 which further includes~~  
Apparatus for adjusting printhead-to-media spacing in a printer having a frame and a  
shiftable printhead-carrying carriage mounted on the frame for lateral movement  
relative to the frame, the apparatus comprising:  
a first stationary mechanical contact actuator anchored to the frame and  
disposed beyond one end of a print-job range;  
a first movable mechanical contact actuator movable with the carriage,  
positioned toward that side of the carriage which generally faces the first stationary  
actuator, and engageable with the first stationary actuator during movement of the  
carriage beyond the one end of the print-job range to cause a positional adjustment  
of the carriage which effects a change in printhead-to-media spacing; and  
a rotatable component, and  
wherein said first stationary actuator includes a projection mounted on an  
elongate rail which at least partially supports the carriage during lateral movement,

Page 2 - AMENDMENT  
Serial No. 10/699,432  
HP Docket No. 10011423-2  
KH Docket No. HPCC 3A6A

and the first movable actuator takes the form of a rotation-implementing first cam drivingly joined to the rotatable component, and engageable with the projection during movement of the carriage beyond the one end of the print-job range to cause rotation of the rotatable component.

3. (Original) The apparatus of claim 2, wherein the rotatable component carries a rotatable bearing structure which rotates between positions of engagement and non-engagement with the rail during rotation of the rotatable component, and wherein the position of engagement produces one printhead-to-media spacing, and the position of non-engagement produces another printhead-to-media spacing.

4. (Original) The apparatus of claim 2, wherein the rotatable component takes the form of an elongate shaft mounted on the carriage for a rotation about a long axis of the shaft, and wherein the shaft carries rotatable bearing structure that includes an elongate finger which extends radially relative to the shaft such that the finger, with rotation of the shaft, selectively engages and disengages the rail to effect a change in printhead-to-media spacing.

5. (Original) The apparatus of claim 4, wherein the first cam includes an axially outwardly facing, at least partially helical, cam surface that is contactable with the projection.

6. (Currently Amended) ~~The apparatus of claim 4,~~ Apparatus for adjusting printhead-to-media spacing in a printer having a frame and a shiftable printhead-carrying carriage mounted on the frame for lateral movement relative to the frame, the apparatus comprising:

a first stationary mechanical contact actuator anchored to the frame and disposed beyond one end of a print-job range; and

Page 3 - AMENDMENT  
Serial No. 10/699,432  
HP Docket No. 10011423-2  
KH Docket No. HPCC 3A6A

a first movable mechanical contact actuator movable with the carriage, positioned toward that side of the carriage which generally faces the first stationary actuator, and engageable with the first stationary actuator during movement of the carriage beyond the one end of the print-job range to cause a positional adjustment of the carriage which effects a change in printhead-to-media spacing;

wherein the carriage is adjustable via a rocking motion to establish different printhead-to-medium spacings, the first stationary actuator includes a plate structure joined to the frame, and the first movable actuator includes a spring-biased push-button and a rotary ratchet wheel rotatably mounted on the carriage, and an elongate movable finger drivingly associated with the wheel, and collectively therewith exhibiting bi-stable behavior in relation to successive engagements occurring between the push-button and the plate structure, such bi-stable behavior creating alternating rocking of the carriage to establish different selected printhead-to-media spacings.

7. (Cancelled)

8. (New) Apparatus for adjusting printhead-to-media spacing in a printer having a frame and a shiftable printhead carriage mounted for movement relative to the frame, the apparatus comprising:

a stationary actuator, fixed relative to the frame and disposed beyond an end of a print range,

bearing structure mounted on the carriage and engageable with an elongate rail during movement of the carriage to define printhead-to-media spacing; and

a movable actuator engageable with the stationary actuator during movement of the carriage beyond the end of the print range, such engagement being effective

Page 4 - AMENDMENT  
Serial No. 10/699,432  
HP Docket No. 10011423-2  
KH Docket No. HPCC 3A6A

to cause a positional adjustment of the bearing structure relative to the carriage, and thereby, to effect a change in printhead-to-media spacing.

9. (New) The apparatus of claim 8, wherein the movable actuator includes a cam drivingly joined to the bearing structure and engageable with the stationary actuator during movement of the carriage beyond the end of the print range to cause adjustment of the bearing structure.

10. (New) The apparatus of claim 9, wherein the bearing structure includes a rotatable finger that selectively engages and disengages the rail to effect a change in printhead-to-media spacing.